

SKU: **2D-APK82**



## Face reader terminal

Face reader access control terminal integrates certificate ID, facial recognition with TCP/IP communication. All terminals can be managed by internet to control lock and realized data backup.

We can set verification mode by 1:1 or 1:N.

## Application

- Higher access control level for office building, zone entrance management.
- Time attendance and visitor management
- Door access control management by using facial recognition.

## Features

- Dual cameras, dual algorithm of 1:1/1:N verification
- Active light source can be visible light and remote infrared light which can prevent environment influence, no harm to human body.
- Dual face algorithms to prevent non alive face recognition.
- Standalone or network
- Ergonomic design

# Parameters



Face reader terminal			
TYPE		DESCRIPTION	
Name		Face reader terminal	
Model no.		2D-APK82	
Operation system		Android 5.0	
Speed		<1 s	
FRR		< 0.01%	
Rejection rate		< 0.1%	
Work mode		Standalone / network	
Hardware specifications	CPU	ContexA17	
	Flash	8-16 GB	
	RAM	2-4 GB DDR3	
	Camera	Dual 2 million cameras	
	Certificate ID	GA/T - 2003 standard	
	Screen	8 inch IPS screen	
		768 X1024/ Capacitive touch	
	Storage	Mico SD	
Extended Capacity	8 - 128 GB		
Verification	User	10000人	
	Mode	1: N / 1:1	
	Anti fake	Support	
	Recognition speed	50 ~100CM	
Device management	Admin suer	support	
	Over capacity alarm	Support	
	Timer	Built in RTC network automatic timing	
I/O interface	Network	RJ45 X 1	
	Wiegand	Wiegand X 1	
	Relay	RelayX 1	
	USB	USB X 1	
	Alert prompt	Alarm prompt X 1	
Wireless config	WIFI	2.4/5G 802.11a/b/g/n/ac	
	4G	Option	
Human computer interaction	voice broadcast	Support	
	Input	English	
	Reset	1	
	Voltage	DC12V /3A	
	Rated power	15W	
	Size	230mm* 150mm* 320mm *	

