

# 2E-M310U Mifare® Card Reader / Writer MF5 Mifare® Read / Write Module

#### Introduction:

The **2E-M310U** is a high performance Mifare® card reader and writer. Multi-application cards can also be used with this read / write unit.

The **MF5** is a tiny Mifare® card read / write module, which is designed for the applications of RFID technology for handy terminal or custom-built for system integrators.

By using **2E-M310U** / **MF5** reader / writer (module) and the encoder software, customers can implement their own applications and define security keys themselves.

#### Features:

- Fast data transfer
- High data integrity
- True anti-collision
- MF5 read / write module for handy terminal or custom-built.

### **Applications:**

- Pre-payment, Ticketing
- Prepaid parking / meal coupon
- Multi-application: Tracking, Retail, Customer, Loyalty, Leisure, Gambling

## **Specifications:**

|                             | 2E-M310U                                    | MF5   |
|-----------------------------|---|---|
| Major Feature               | Programmer for card issue                   | Read / Write module                         |
| RF Frequency                | 13.56 MHz                                   | 13.56 MHz                                   |
| RF Distance                 | 2 cm  | Depends on antenna                          |
| DC Power                    | 5 V / 100 mA                                | 5 V / 100 mA                                |
| Interface                   | USB<br>RS232, 19200, N, 8, 1                | RS232, 19200, N, 8, 1                       |
| Protocol                    | GNET PLUS                                   | GNET PLUS                                   |
| Card Type                   | ISO 14443 A<br>Mifare® Class<br>Mifare® PRO | ISO 14443 A<br>Mifare® Class<br>Mifare® PRO |
| Memory                      | 32 KB                                       | NO  |
| Dimension (mm)              | W 65 x L 100 x D 24.7                       | W 26 x L 36 x H11                           |
| Housing                     | ABS   | No  |
| Weight                      | 115 g                                       | 10 g  |
| Operating temperature       | -10 ~ +60° C                                | -10 ~ +60° C                                |
| Operating relative humidity | 10 ~ 90 %                                   | 10 ~ 90 %                                   |

## **Ordering Information:**

PCR310U: USB interface with read / write software

PCR310R: RS232 interface with read / write software

MF5 + Start Kit : Development kit with read / write software

MF5: Read / Write Module only

 $\divideontimes$  Mifare is a registered trademark of Philips Electronics N.V.

Specification is subject to change without notice.



