



Camara PTZ IP de 2 MP 1A-9620

- 1/3" Progressive scan CMOS, 20 x optical zoom
- HD network video output:
- 1920*1080@25fps(PAL)/30fps(NTSC)
- H.264 image compression format
- TCP/IP, UDP, DHCP, DDNS, NTP, RTSP, SMTP, FTP, PPPoE support
- SD card local storage, network remote storage
- Web GUI menu
- Support frame selection zoom in function
- Provide standard SDK, easy to integrate with other digital

system

- CVBS video output: 1CH HD-SDI, 1CH CVBS
- IP66 weather-proof:
- 4KV lightning protection,
- Surge protection

Specifications:

Model	1A-9620	
Camera	Image sensor	1/3" Progressive CMOS
	Image pixels	1920x1080
	Horizontal resolution	2 MP
	Min.Illumination	0.5Lux(Day), 0.1Lux(Night), 0.05Lux(DSS ON)
	WB	Auto/Manual
	S/N Ratio	> 50dB
	Day/night	Auto/Manual/Timing
	Focus mode	Auto/Manual
	Lens	20xZoom, f=4.7~94mm, F1.6~F3.5



PTZ	Pan range	360 endless rotation
	Pan speed	Preset Speed: 400° /S: Manual Control Speed:0.5~120° /S
	Tilt range	0~90° (auto rotation)
	Tilt speed	Preset Speed: 400° /S: Manual Control Speed:0.5~90 °/S
System	PTZ control	Support
	Preset	255
	Patrol	8
	Trace	4
	Time Task	8
	Scan	2
	Home position display	Support
	Auto Flip	Support
	Alarm input	4CH
	Alarm output	1CH(NC/NO)
	Alarm linkage	Support
	Power consumption	9W(max.24W,Heater on)
	Power supply	AC24V/DC12V
	Working environment	Temperature:-20°C ~ 60°C ; Humidity:less than 95%
Protection level	IP66	
Weight	5KG	
Network	Compression	H.264
	Frame rate	1~30FPS(25FPS)
	Protocal	TCP/IP,UDP,DHCP,DDNS,NTP,RTSP,SMTP,FTP,PPPoE
	Storage	SD card local storage,network remote storage
	Smart alarm	Motion ,Sensor
	Resolution	1920*1080,1280*720,640*480,320*240,160*120
	Multi-stream	Support
Port	Network interface	10Base-T/100Base-TX,RJ45
	Audio	Mic input*1,Mic output*1
	Analog output	CVBS



ONE TECH