



SC-32DO2B | L series

2MP Pinhole HD Analog Camera



- 1/2.9" 2MP CMOS Sensor
- AHD/TVI/CVI/CVBS Video Output
- High Quality Lens 3.7mm
- Lightning Protection Up to 2KV



System Overview

L series Pinhole HD analog camera adopts advanced 4-in-1 ISP and 1/2.9" image sensor, featured by the excellent image details with wide FOV. It offers built-in UTC function to switch the signal output flexibly among the 4 popular technologies. It's ideal solution for SMB solution with high cost-performance ratio and simplicity for installation.

Functions

Long Distance Transmission

Powered by leading HD Videoloss technology, it supports up to 500m/800m transmission over RG59/RG6 coaxial cables separately.

Advanced 4 in 1 technology

L series is built in with advanced 4 in 1 technology, it's equipped with UTC chipset on board which could support to adjust HD analog signal output flexibly, such as AHD/TVI/CVI/CVBS. It's the final solution for true plug-n-play to work with any brand of HD analog DVR seamlessly.

Technical Parameters

Camera

Model	SC-32D02B	Min. Illumination	Color: 0.01Lux@F1.2, AGC ON
Image Sensor	1/2.9" 2MP Sensor	Effective Pixels	1920(H)* 1080(V)
Scanning System	Progressive	S/N Ratio	More than 52dB

Lens

Focal Length	3.7mm	FOV	90°
Aperture	F2.0		

Video

Video Output	AHD/TVI/CVI/CVBS	WDR	DWDR
Resolution	25/30fps@1080P	AGC	Supported
OSD Menu	Supported	White Balance	Supported
BLC	Supported	Noise Reduction	3D DNR

General

Working Temperature	-10 C ~+50 C	Ingress Protection	N/A
Working Humidity	10~90%	Dimensions	41 (L)*22.2(W)*56.6 (H)mm
Power Supply	DC12V±10%	Net Weight	0.1KG
Power Consumption	<3.2W	Gross Weight	0.15KG

Ordering Information

Type	Part Number	Description
2MP Camera	SC-32D02B	2MP Pinhole HD Analog Camera

Dimensions (mm)

